

DATA SHEET

Polycom[®] Video Border Proxy[™] (VBP[®]) Series

Easily and securely connect video participants in and outside the firewall and optimize for the best collaboration experience

Polycom® RealPresence® Firewall Traversal and Security solutions remove communication barriers and allow teams to collaborate more effectively over video. Leveraging existing security investments, these solutions provide a trusted route for external users into room and personal telepresence as well as into traditional video conferences. RealPresence Firewall Traversal and Security solutions deliver business-grade video quality through efficient services delivery, which identifies and prioritizes business applications.

The Polycom VBP Series supports all standards-based telepresence solutions, video conferencing endpoints and multipoint conference bridges. Using standards-based firewall traversal, secure access is provided to users of Polycom Converged Management Application™ Desktop (CMAD®), Polycom RealPresence® Mobile and and Polycom® HDX® Series telepresence solutions without requiring a Virtual Private Network (VPN).

The Polycom VBP Series dramatically improves visual quality through unique bandwidth management which identifies and accelerates video traffic in the shortest path including prioritized video traffic management, traffic shaping, call admission control, and DiffServ marking/policing. With availability for bandwidths from 1 Mbps to 200 Mbps, the Polycom VBP Series is also configurable for centralized or decentralized dial plans, depending on IT requirements.

Remote Access: VBP ST Solutions 6400 and 5300

Polycom VBP ST solutions enable seamless, secure, collaboration experiences for the virtual workforce. Easy to use and manage, the ST solutions provide access for every remote user who needs to securely collaborate, as well as versatile networking and security solutions that protect communication investments.

B2B Communications: VBP E Solutions 6400, 5300, 4555, and 200 E

Polycom VBP E solutions enable and enhance intra- and inter-office video collaboration. VBP E solutions provide versatile networking and security that protect communication investments.



Benefits

- Accelerate ROI in existing networks by easily extending telepresence and video to new groups of users
- Increase communication quality with customers, partners, and remote colleagues
- Reduce the impact of telepresence and video on the network with secure traffic optimization
- Interoperable with all standardsbased video endpoints, gatekeepers, and multipoint conferencing platforms

The Polycom Video Border Proxy™ (VBP®) NAT/Firewall traversal solutions supplant or integrate with existing firewalls giving remote users a trusted route into room and personal telepresence and traditional video conferences, as well as allow organizations to collaborate securely with other organizations via video. Quality is optimized by prioritizing video traffic over data traffic, providing both shortest-path routing and traffic shaping.

Network Security

- Application Layer Gateway dynamically provisions (opens and closes) UDP ports used for video and voice calls
- NAT/PAT server hides enterprise LAN topology
- Dynamic Whitelist/Blacklist for RealPresence Mobile, CMAD, Dynamic Endpoints
- · Access Proxy Authentication

Dialing Methods for RealPresence Mobile, CMAD, Dynamic Endpoints

E.164, E-mail or Annex O format, IP address, IP address + extension (inbound from the wide area network only)

Embedded Gatekeeper

Gatekeeper neighboring ensures call reliability, and least cost routing in the local or wide area network (E Model)

Deployment Models

- LAN side gatekeeper
- Embedded gatekeeper
- WAN side gatekeeper
- · Gatekeeper Neighboring
- TLS Proxy
- WAN NAT
- Peering Proxy

Polycom Video Border Proxy Series

Model	Performance	Number of Registrations	Embedded Gatekeeper	Access Proxy
200 E	1 Mbps license for video traffic	3	•	•
4555	3 Mbps license for video traffic	15	•	•
5300 E	10 Mbps, 25 Mbps licenses for video traffic	5300 E-10 = 50 5300 E-25 = 100 5300 E-50 = 100 5300 E-85 = 100	٠	٠
5300 ST	10 Mbps, 25 Mbps, 50Mbps, 85Mbps licenses for video traffic	N/A	N/A	•
6400 E	10 Mbps, 25 Mbps, 50Mbps, 85Mbps licenses for video traffic	250	•	•
6400 ST	85 Mbps, 200 Mbps licenses for video traffic	N/A	N/A	•

Polycom VBP 4555

WAN Interfaces

- T1
- ESF/D4 Framing
- B8ZS/AMI Line Coding
- 0, -7, -15db Line Build Out

Ethernet WAN

- 1 x 10/100 Mbps
- · Auto Sensing
- RJ-45
- · Half or Full Duplex
- PPoE

Ethernet LAN

- 4 x 10/100 Mbps
- Auto Sensing
- RJ-45
- Half or Full Duplex
- Managed VLAN

Dimensions

• Height: 1.7", Width: 10", Depth: 7"

Weight

2 lbs

Power

• External Brick (AC)- 12V, 3.0A

Power Consumption

• 32W (Maximum)

Emissions

- FCC Part 68, FCC Part 15 Class A, ICES-003, VCCI Class A, KCC, C-tick
- Immunity
- CE

Safety

· CE, UL

Certifications

 $\bullet \ \ {\sf RoHS \ Compliant}, \ {\sf WEEE \ Compliant}$

Polycom VBP 5300LF2

Interfaces

- Ethernet WAN: 1 x 10/100/1000 Mbps
- Ethernet LAN: 1 x 10/100/1000 Mbps
- Ethernet Management: 1 x 10/100/1000 Mbps
- Serial: 1 x RS 232

Dimensions

• Height: 1.73", Width: 17.4", Depth: 11.5"

Weight

• 13 lbs

Power

• 100/240v VAC, auto-selecting, 50 to 60 Hz

Power Consumption

200W (Maximim)

Emissions

 FCC Part 15 Class A, ICES-003, VCCI Class A, KCC, CCC, C-tick

Immunity

CE

Safety

• CE, cUL

Certifications

• RoHS Compliant, WEEE Compliant, Gost R

Polycom VBP 6400LF2

Interfaces

- Ethernet WAN: 1 x 10/100/1000 Mbps
- Ethernet LAN: 1 x 10/100/1000 Mbps
- Ethernet Management: 1 x 10/100/1000 Mbps
- Serial: 1 x RS 232

Dimensions

• Height: 3.45", Width: 17.14", Depth: 20"

WEEE Weight

• 45 lbs

Shipping Weight

• 55.2 lbs

Power

• 100/240v VAC, auto-selecting, 50 to 60 Hz

Power Consumption

• 1080W (Maximum)

Regulatory

 FCC Class A, CE, UL, EMS, VCCI, GS Mark, Gost R, Korean MIC and RoHS



About Polycom

Polycom is the global leader in standards-based unified communications (UC) solutions for telepresence, video, and voice powered by the Polycom® RealPresence® Platform. The RealPresence Platform interoperates with the broadest range of business, mobile, and social applications and devices. More than 400,000 organizations trust Polycom solutions to collaborate and meet face-to-face from any location for more productive and effective engagement with colleagues, partners, customers, specialists, and prospects. Polycom, together with its broad partner ecosystem, provides customers with the best TCO, scalability, and security for video collaboration, whether on-premises, hosted, or cloud-delivered. Visit www.polycom.com or connect with Polycom on Twitter, Facebook, and LinkedIn.

Polycom, Inc. 1.800.POLYCOM www.polycom.com Polycom Asia Pacific Pte Ltd +65 6389 9200

www.polycom.asia

Polycom EMEA +44 (0)1753 723282 www.polycom.co.uk

